



**FOTHERGILL  
COATED  
FABRICS LTD**

## Technical Data Sheet

**Product**                      **03-212/00**  
**Description**                **Non Stick, Coated Glass Fabric**

<b>Typical Properties</b>	<b>Nominal Values</b>	<b>Test Method</b>
<b>Thickness (mm)</b>	<b>0.236</b>	
<b>Weight (g/m<sup>2</sup>)</b>	<b>485</b>	
<b>% PTFE Coating</b>	<b>58</b>	
<b>Warp Tensile Strength (N/5cm)</b>	<b>2500</b>	<b>BS3424: Part 4</b>
<b>Warp Tongue Tear Strength (N)</b>	<b>30</b>	<b>BS3424: Part 5</b>
<b>Coating Adhesion (N/ 5cm)</b>	<b>N.A</b>	<b>BS3424: Part 7</b>
<b>Surface Resistance ( <math>\Omega</math> / m<sup>2</sup> )</b>	<b>Insulative</b>	
<b>Operating Temperature ( <math>\square</math> C )</b>	<b>- 72 to + 260</b>	

Fothergill Coated Fabrics reserves the right to alter any of the elements quoted in the above specification without prior notice. Please note that the above information is given in good faith and should be considered as a guide only. Suitability of the product for all applications is at the discretion of the user.

**Issue number 2**

**Date: 6<sup>th</sup> July, 2009**