



MEDIUM DUTY AIR HOSE

- TUBE** : Air, water and oil mist resistant, smooth, black SBR/NBR
- REINFORCEMENT** : High tensile synthetic cord
- COVER** : Abrasion, weather and ozone resistant, smooth, cloth impression, black SBR/EPDM
- APPLICATION** : Used in construction and mining industries; for pneumatic tools such as rock drills
- TEMPERATURE** : -30 C°/+85 C° (-22 F°/+185F°)
- REMARKS** : Standard EN ISO 2398; upon request also available in yellow cover

CODE	ID		OD		WP		BP		W	BR	L
	Inch	mm	mm	mm	bar	psi	bar	psi			
MA-020-013-V	1/2	13	23	20	20	300	60	900	400	100	20-40
MA-020-016-V	5/8	16	26	20	20	300	60	900	460	120	20-40
MA-020-019-V	3/4	19	31	20	20	300	60	900	620	160	20-40
MA-020-025-V	1	25	37	20	20	300	60	900	730	200	20-40
MA-020-032-V	1 1/4	32	46	20	20	300	60	900	1210	255	20-40
MA-020-038-V	1 1/2	38	52	20	20	300	60	900	1450	300	20-40
MA-020-051-V	2	51	67	20	20	300	60	900	2090	410	20-40
MA-020-063-V	2 1/2	63	80	20	20	300	60	900	2540	500	20-40
MA-020-076-V	3	76	93	20	20	300	60	900	3250	600	20-40
MA-020-090-V	3 1/2	90	108	20	20	300	60	900	3750	720	20-40
MA-020-102-V	4	102	120	20	20	300	60	900	4100	800	20-40