

## PLASTER / GROUTING HOSE

ER / GROUTING HOSE 40 BAR W.P.

- TUBE** : High abrasion resistant conductive black NR/BR  
**REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire.  
**COVER** : Weather, ozone resistant, abrasion resistant, cloth impression, black SBR/EPDM  
**APPLICATION** : Used for plaster and grouting services  
**TEMPERATURE** : -30 C° / +70 C° (-22 F° / +158F°)  
**REMARKS** : Abrasion loss value acc. DIN 53516 below 50mm3

CODE	ID		OD	WP		BP		W	BR	L
	inch	mm	mm	bar	psi	bar	psi	gr/mt	mm	mt
MF-020-013-VO	1/2	13	27	40	600	120	1800	550	100	20-40
MF-020-019-VO	3/4	19	33	40	600	120	1800	750	160	20-40
MF-020-025-VO	1	25	39	40	600	120	1800	930	200	20-40
MF-020-032-VO	1 1/4	32	46	40	600	120	1800	1130	255	20-40
MF-020-038-VO	1 1/2	38	54	40	600	120	1800	1370	300	20-40
MF-020-051-VO	2	51	68	40	600	120	1800	1800	410	20-40
MF-020-063-VO	2 1/2	63	80	40	600	120	1800	2800	500	20-40
MF-020-076-VO	3	76	94	40	600	120	1800	3400	600	20-40
MF-020-102-VO	4	102	120	40	600	120	1800	4250	800	20-40
MF-020-127-VO	5	127	145	40	600	120	1800	5400	1000	20-40
MF-020-152-VO	6	152	169	40	600	120	1800	5900	1200	20-40