

PH472 - STEAM 2 W/B

Applicable Standard : Exceeds IS 10655 TYPE 3/ ISO 6134 TYPE 2A/ BS 5342 TYPE 2A



Construction :

Inner tube : Black colour, EPDM rubber resistant to high temperature steam

Reinforcement : Double steel wire Braids

Cover : Red Colour, EPDM rubber resistant to heat and weather. Black colour option available on request

Application : High temperature steam Lines at constant pressure of 290 psi

Cover Options

PH482 : Oil resistance outer cover conforms ISO 6134 Type 2B/BS 5342 Type 2B

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r			kg/m		
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	5.1			
PH472-06	-06	1	3/8	10.0	19.5	0.91	23.0	18	260	18	2610	18	130	5.9	150	0.421
PH472-08	-08	0	1/2	12.5	1.18	30.0	1.45	260	18	260	2610	0	9.1	230	11.8	0.589
PH472-12	-12	1	3/4	19.0	36.8	1.71	43.5	18	260	18	2610	18	300	14.8	375	0.846
PH472-16	-16	2	1	25.4	1.95	49.5	2.52	260	18	260	2610	0	17.9	455	23.6	1.095
PH472-20	-20	1	1.1/	31.5	64.0	3.27	83.0	18	260	18	2610	18	600	26.6	675	1.505
PH472-24	-24	9	4	38.0	3.86	98.0		260	18		2610	0	28.5	725		1.780
PH472-32	-32	2	1.1/	51.0							2610	18				2.261
PH472-40	-40	5	2.2	63.0							2610	0				4.214
PH472-48	-48	3	2.1/	76.0							2610	18				4.962



Temperature Range : Continuous: Up to +230°C Steam

2	23	0
8		0
5		18
1		0
6		18
3		0
7		18
6		0