

Airprene 150°C



Applications:

Suction of hot air and fumes in chemical plants.

Properties:

Flexible duct made in thermoplastic rubber with a steel spiral reinforcement embedded between the two layers.

For use in high temperature till 150°C

Light and flexible is extremely resistant to high temperatures, chemicals and abrasion. UV- protections added

Standard Color:

Black

Temperatures Range:

-40°C < Temp +150°C

Code	Internal Diameter		wall Thickness +/- 0.2 mm	Weight gr / m ± 10%	Vacuum MH ₂ O	Bending Radius mm	Roll Length m
	mm	Inch					
AP-140	40		0.4	200	2.0	32	20
AP-200	51	2"	0.4	250	2.0	40	20
AP-250	63	2 ½"	0.4	310	1.7	55	20
AP-300	76	3"	0.5	460	1.7	65	20
AP-350	90	3 ½"	0.5	580	1.6	75	20
AP-400	102	4"	0.6	610	1.3	85	10/15/20
AP-500	127	5"	0.65	830	1.0	105	10/15/20
AP-600	152	6"	0.65	1010	0.8	125	10/15/20
AP-800	203	8"	0.65	1480	0.4	165	15
AP-1000	254	10"	0.65	1930	0.4	210	10
AP-1200	305	12"	0.65	2380	0.3	250	10



sizes are available upon request.