

Applications:

Heating and ventilation systems, delivery and suction of air, smoke, gas, dust.

Properties:

Flexible duct hose made of flame resistant PVC coated polyester fabric and reinforced with a steel helix welded between the two layers.

Flame-retardant according to UL 94-V0, M2 standards.

Compacted to 85% of its length. Internally and externally sinuous. UV resistance

Standart Colors:

Grey

Temperatures Range:

-15°C < Temp <70°C, 110°C for short term only

Standards:

Tolerance: ISO 1307
Flame-retardant M2, UL 94-V0
RoHS, Reach Standard

Code	Internal Diameter		Wall thickness +/-0.2 mm	Spiral pitch +/- 2 mm	Vacuum MH ₂ O	Bending Radius mm	Roll Length +/- 0.10 m
	mm	Inch					
VR-050	50	2"	0.22	12	0.95	26	10
VR-060	60		0.22	16	0.90	30	10
VR-063	63	2 1/2"	0.22	16	0.90	32	10
VR-070	70		0.22	16	0.85	35	10
VR-076	76	3"	0.22	16	0.80	40	10
VR-080	80		0.22	16	0.75	40	10
VR-090	90		0.22	20	0.70	45	10
VR-102	102	4"	0.22	20	0.65	51	10
VR-125	125	5"	0.22	20	0.45	64	10
VR-152	152	6"	0.22	20	0.35	76	10
VR-200	200	8"	0.22	20	0.20	102	10
VR-250	250	10"	0.22	32	0.12	127	10
VR-300	300	12"	0.22	32	0.05	153	10

