

Applications:

Light duty suction and transportation of liquids. Designed for industry and agriculture.

Properties:

Flexible PVC hose, reinforced with a shock resistant rigid PVC spiral
Excellent resistance to weather conditions and most chemicals.
Smooth Bore

Standart Colors:

Transparent-Green with a White spiral (available in various colors on request)

Materials:

DOP Free
RoHS, Reach Standard,
UV- protections added

Temperatures Range:

-15°C < Temp < 60°C

Standard:

Tolerance: ISO 1307

Code	Internal Diameter		Weight gr / m	Work Pressure Bar / 20°C	Bending Radius mm	Vacuum MH ₂ O	Roll Length m
	mm	Inch					
W-034	19	¾"	220	7	85	7	50
W-078	22	7/8"	260	7	100	7	50
W-100	25	1"	250	6.5	105	7	50
W-130	30	1 ¼"	340	6	120	7	50
W-125	32	1 ¼"	345	6	130	7	50
W-150	38	1 ½"	470	6	155	7	50
W-140	40		500	5.5	165	7	50
W-145	45		550	5.5	195	7	50
W-148	48		680	5	205	7	50
W-200	51	2"	680	5	205	7	50
W-260	60		950	4	250	7	50
W-250	63	2 ½"	980	4	260	7	50
W-270	70		1000	4	295	7	50
W-300	76	3"	1150	4	320	6	50
W-380	80		1200	3	335	6	50
W-350	89	3 ½"	1800	3	390	6	50
W-400	102	4"	2000	3	430	6	30
W-450	114	4 ½"	2500	2.5	475	6	30
W-500	127	5"	2800	3	630	5	30
W-600	152	6"	4050	3	715	5	30
W-700	178	7"	4400	2	850		10
W-800	203	8"	5500	2	900		10



sizes are available upon request.

