



XLPE CHEMICAL SUCTION AND DELIVERY HOSE

TUBE: Chemical and solvent resistant translucent XLPE.

REINFORCEMENT: High tensile synthetic cord with wire helix and antistatic copper wires.

COVER: Weather, ozone resistant and abrasion resistant, smooth, cloth impression, green EPDM.

APPLICATION: Used for suction and discharge of chemicals and acids

TEMPERATURE: -30 C° / + 80 C° (-22 F° / + 176 F°)

REMARKS: Upon request oily environment resistant CR cover available.



CODE	inch	mm	mm	bar	psi	bar	psi	Gr/mt	mm	mt
MX-010-019-AX	3/4	19	31	10	150	40	600	660	120	20-40
MX-010-025-AX	1	25	37	10	150	40	600	800	150	20-40
MX-010-032-AX	1.1/4	32	44	10	150	40	600	1050	200	20-40
MX-010-038-AX	1.1/2	38	51	10	150	40	600	1320	230	20-40
MX-010-051-AX	2	51	65	10	150	40	600	1850	300	20-40
MX-010-063-AX	2.1/2	63	79	10	150	40	600	2640	380	20-40
MX-010-076-AX	3	76	92	10	150	40	600	3200	460	20-40
MX-010-102-AX	4	102	118	10	150	40	600	4200	600	20-40