

# GUMI

Material: Aluminum Alloy      Method: Gravity Casting  
 Surface Finish: T6 Heat treatment      Handle: Brass & Stainless steel  
 Gasket: NBR      Safety Pin: Steel  
 Thread: ISO228(BSP)/ISO7(BSP)/ANSI B1.20(NPT)      Standard: MIL A-A-59326 / EN14420-7(DIN2828)

**STYLE**  
TYPE A



MALE ADAPTER  
X  
FEMALE THREAD

SIZE	CODE
1/2"(DN15)	A050-AL
3/4"(DN20)	A075-AL
1"(DN25)	A100-AL
1-1/4"(DN32)	A125-AL
1-1/2"(DN40)	A150-AL
2"(DN50)	A200-AL
2-1/2"(DN65)	A250-AL
3"(DN80)	A300-AL
4"(DN100)	A400-AL
5"(DN125)	A500-AL
6"(DN150)	A600-AL
8"(DN200)	A800-AL

**STYLE**  
TYPE E



MALE ADAPTER  
X  
HOSE SHANK

SIZE	CODE
1/2"(DN15)	E050-AL
3/4"(DN20)	E075-AL
1"(DN25)	E100-AL
1-1/4"(DN32)	E125-AL
1-1/2"(DN40)	E150-AL
2"(DN50)	E200-AL
2-1/2"(DN65)	E250-AL
3"(DN80)	E300-AL
4"(DN100)	E400-AL
5"(DN125)	E500-AL
6"(DN150)	E600-AL
8"(DN200)	E800-AL

**STYLE**  
TYPE B



FEMALE COUPLER  
X  
MALE THREAD

SIZE	CODE
1/2"(DN15)	B050-AL
3/4"(DN20)	B075-AL
1"(DN25)	B100-AL
1-1/4"(DN32)	B125-AL
1-1/2"(DN40)	B150-AL
2"(DN50)	B200-AL
2-1/2"(DN65)	B250-AL
3"(DN80)	B300-AL
4"(DN100)	B400-AL
5"(DN125)	B500-AL
6"(DN150)	B600-AL
8"(DN200)	B800-AL

**STYLE**  
TYPE F



MALE ADAPTER  
X  
MALE THREAD

SIZE	CODE
1/2"(DN15)	F050-AL
3/4"(DN20)	F075-AL
1"(DN25)	F100-AL
1-1/4"(DN32)	F125-AL
1-1/2"(DN40)	F150-AL
2"(DN50)	F200-AL
2-1/2"(DN65)	F250-AL
3"(DN80)	F300-AL
4"(DN100)	F400-AL
5"(DN125)	F500-AL
6"(DN150)	F600-AL
8"(DN200)	F800-AL

**STYLE**  
TYPE C



FEMALE COUPLER  
X  
HOSE SHANK

SIZE	CODE
1/2"(DN15)	C050-AL
3/4"(DN20)	C075-AL
1"(DN25)	C100-AL
1-1/4"(DN32)	C125-AL
1-1/2"(DN40)	C150-AL
2"(DN50)	C200-AL
2-1/2"(DN65)	C250-AL
3"(DN80)	C300-AL
4"(DN100)	C400-AL
5"(DN125)	C500-AL
6"(DN150)	C600-AL
8"(DN200)	C800-AL

**STYLE**  
TYPE DC



DUST CAP

SIZE	CODE
1/2"(DN15)	DC050-AL
3/4"(DN20)	DC075-AL
1"(DN25)	DC100-AL
1-1/4"(DN32)	DC125-AL
1-1/2"(DN40)	DC150-AL
2"(DN50)	DC200-AL
2-1/2"(DN65)	DC250-AL
3"(DN80)	DC300-AL
4"(DN100)	DC400-AL
5"(DN125)	DC500-AL
6"(DN150)	DC800-AL
8"(DN200)	DC800-AL

**STYLE**  
TYPE D



FEMALE COUPLER  
X  
FEMALE THREAD

SIZE	CODE
1/2"(DN15)	D050-AL
3/4"(DN20)	D075-AL
1"(DN25)	D100-AL
1-1/4"(DN32)	D125-AL
1-1/2"(DN40)	D150-AL
2"(DN50)	D200-AL
2-1/2"(DN65)	D250-AL
3"(DN80)	D300-AL
4"(DN100)	D400-AL
5"(DN125)	D500-AL
6"(DN150)	D600-AL
8"(DN200)	D800-AL

**STYLE**  
TYPE DP



DUST PLUG

SIZE	CODE
1/2"(DN15)	DP050-AL
3/4"(DN20)	DP075-AL
1"(DN25)	DP100-AL
1-1/4"(DN32)	DP125-AL
1-1/2"(DN40)	DP150-AL
2"(DN50)	DP200-AL
2-1/2"(DN65)	DP250-AL
3"(DN80)	DP300-AL
4"(DN100)	DP400-AL
5"(DN125)	DP500-AL
6"(DN150)	DP800-AL
8"(DN200)	DP800-AL





Rubber Products, Engineering plastics and industrial sealing solutions

10 Hamashbir Street, Industrial Area Holon 58855, Tel: +972.3.5599703/7357700

Fax: +972.3.5582111/5599702, P.O. box 1858, Holon 58117,

Email: [gumi@gumi.co.il](mailto:gumi@gumi.co.il) Web Site: [www.gumi.co.il](http://www.gumi.co.il)

# GUMI

型号 (type)	规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
<b>TYPE-A</b>  五金 五金配件 溪市宗汉建业五金配件厂	规格 (size)	50	75	100	125	150	200	250	300	400	500	600
	规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
	A	26	32.4	38.5	48.5	56	66	82	96	122.5	152	181
	B	37	41	51.6	55	56	59	80	71.7	73.8	75.5	69.8
	C	16.5	21.5	24	29	37.8	47.1	58	74.4	101	125	150
To equip with "B" or "C" or "D" or "DC"												
<b>TYPE-B</b>  五金配件 溪市宗汉建业五金配件厂	规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
	A	14	18	25	32	38.5	49	60	77	100	125	151
	B	44	52.2	59	65.5	69.5	77	84.5	89.5	92	93	103.75
	E	28	33.2	39.9	45.5	46	52.5	55.5	58	59	60	62.75
To equip with "A" or "E" or "F" or "DP"												
<b>TYPE-C</b>  五金配件 溪市宗汉建业五金配件厂	规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
	A	8	14	19.5	25.3	36.8	43	56	66.2	91.8	117	142
	B	70	80	94.9	102.5	116.5	134.5	142.5	143	162.5	192	234.3
	D	14	21.5	27.4	34.1	39.6	52.4	66.6	77.8	103.2	129	154
	E	29	33.2	39.9	45.5	46	52.5	55.5	58	59	60	62.75
To equip with "A" or "E" or "F" or "DP"												
<b>TYPE-D</b>  五金配件 溪市宗汉建业五金配件厂	规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
	A	26	32.41	40.49	50.8	53.98	68.27	80.98	92.2	125.4	150.8	181
	B	43	52.2	59	67.5	69.5	76	84.5	89.5	92	96	99.75
	E	29	33.2	39.9	45.5	46	52.5	55.5	58	59	60	62.75

Rubber Products, Engineering plastics and industrial sealing solutions

10 Hamashbir Street, Industrial Area Holon 58855, Tel: +972.3.5599703/7357700

Fax: +972.3.5582111/5599702, P.O. box 1858, Holon 58117,

Email: gumi@gumi.co.il Web Site: www.gumi.co.il

# GUMI



To equip with "A" or "E" or "F" or "DP"

规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
A	8	18.7	19.5	31.3	30.8	43	56	74	91.8	117	142
B	74	85.3	100.8	109	123.5	142	150.5	157	170.5	207	248
C	24	32.1	36.73	45.52	53.34	63.09	75.82	91.5	119.6	145.2	175.99
D	14	21.5	27.4	34.1	39.6	52.4	66.6	77.8	103.2	129	154
E	23	26	33.8	39	41	46	48	50	52.8	53	57.3
F	41	47.8	55	57	70.5	82	87	92	103.5	132	171.5

To equip with "B" or "C" or "D" or "DC"

规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
A	15	18	25	32	38.5	49	60	77	100	125	150
B	49	55	67.8	78	76	83.5	97	99.5	105.8	112.5	129.8
C	26	32.1	36.7	45.52	53.34	63.09	75.7	91.5	119.5	150	181
E	25	26	34.8	40	41	46	50	51	53.8	53	57.3

To equip with "B" or "C" or "D" or "DC"

规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
A	29	33.2	39.9	45.5	46	51.5	55.5	58	59	60	62.75
B	36	43.2	54.9	60.5	49.5	66.5	70.5	73	74	80	90.75

To equip with "A" or "E" or "F" or "DP"

规格 (size)	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	5"	6"
B	25	36	49.5	55	54.5	61	65	64	65.8	73	85.3
E	34	26	34.8	40	41	46	50	49	50.8	53	57.3

To equip with "B" or "C" or "D" or "DC"

**Rubber Products, Engineering plastics and industrial sealing solutions**

10 Hamashbir Street, Industrial Area Holon 58855, Tel: +972.3.5599703/7357700

Fax: +972.3.5582111/5599702, P.O. box 1858, Holon 58117,

Email: [gumi@gumi.co.il](mailto:gumi@gumi.co.il) Web Site: [www.gumi.co.il](http://www.gumi.co.il)



**Specifications:**

Size: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"

Body: Aluminum, Brass, Bronze, Stainless Steel, Polypropylene

Handles: Brass or Stainless Steel

**Gaskets:**

Material	Color Code	Temperature Ratings
Buna-N	Blue	-40 F to 212 F
Neoprene	Red	-60 F to 225 F
EPDM	White	-60 F to 275 F
Viton	Yellow	-20 F to 500 F
Teflon		-40 F to 250 F

Manufactured to Mil Spec 27487 tolerances. Interchangeable with all major brands.

**Maximum Operating Pressure:**

Material	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
Aluminum	250	250	250	250	250	150	125	125	75
Brass	250	250	250	250	250	150	125	125	75
Bronze	250	250	250	250	250	150	125	125	75
Stainless	250	250	250	250	250	150	125	125	75
Polypropylene	125	125	100	100	100	75	75	50	

PSI - At Room Temperature 70F

**Rubber Products, Engineering plastics and industrial sealing solutions**

10 Hamashbir Street, Industrial Area Holon 58855, Tel: +972.3.5599703/7357700

Fax: +972.3.5582111/5599702, P.O. box 1858, Holon 58117,

Email: [gumi@gumi.co.il](mailto:gumi@gumi.co.il) Web Site: [www.gumi.co.il](http://www.gumi.co.il)